

## TIBET

### Product Specifications

<b>Product:</b>	<b>TIBET</b>
<b>Style Number:</b>	<b>92430</b>
<b>Description:</b>	<b>High Low Loop</b>
<b>Fibre Type:</b>	<b>50% Wool 50% Polypropylene</b>
<b>Yarn Construction:</b>	<b>2 ply</b>
<b>Pile Weight:</b>	<b>26oz</b>
<b>Pile Height (High):</b>	<b>1/5"</b>
<b>Pile Height (Low):</b>	<b>5/32"</b>
<b>Machine Gauge:</b>	<b>1/8th</b>
<b>Pattern Repeat:</b>	<b>n/a</b>
<b>Primary Backing:</b>	<b>Polypropylene</b>
<b>Secondary Backing:</b>	<b>Jute</b>
<b>Width:</b>	<b>12'</b>
<b>Rating:</b>	<b>Residential</b>

**Color Line:**

<b>30</b>	<b>Sahara</b>
<b>185</b>	<b>Mocha</b>
<b>305</b>	<b>Llama</b>
<b>330</b>	<b>Kalahari</b>
<b>335</b>	<b>Sudan</b>
<b>510</b>	<b>Pawnee</b>
<b>515</b>	<b>Linen</b>
<b>550</b>	<b>Temple</b>
<b>560</b>	<b>Loofa</b>
<b>580</b>	<b>Suede</b>

**Heavy Duty & Stairs**  
**Commercial Light Duty**

**Surface Flammability:** **Pass**  
(DOC FF-1-70/FF2-70 Methanamine Pill)

**Radiant Panel Test:** **Class One**  
(ASTM E648-97 Radiant Flux of Floor Covering)

**Optical Smoke Density:** **Pass**  
(ASTM E662 Smoke Chamber Test)

**Extractable Matter:** **1.5% Maximum**  
(Dichloromethane Extract AS 2001.3.4)

**Resistance to insect pests:** **Pass**  
(AS 2001.6.1)

The Fernmark on this carpet is your assurance that Wools of New Zealand's stringent specifications for the stated location guide have been met. Tests include wool content, pile weight, appearance retention, durability, resistance to soiling, insect resistance and colorfastness to light and cleaning.

Godfrey Hirst recommends that these carpets be installed according to CRI - 014 - 2002 Standard for Installation of Commercial Carpets. A copy of these guidelines are available online at [www.carpet-rug.com](http://www.carpet-rug.com)

1000 Holcomb Woods Parkway, Suite 118B, Roswell, GA 30076

Tel: (800) 480 7134 Fax: (800) 480 7135

Email: [northamerica.customerservice@godfreyhirst.com](mailto:northamerica.customerservice@godfreyhirst.com)

[www.godfreyhirstusa.com](http://www.godfreyhirstusa.com)